



ALUMINUM BODY SIDE ROLL PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 5/8" SCUFFPLATE ON EACH CAB DOOR JAMB
- 5/8" SCUFFPLATE ON CAB AND DECK CAB INTERIOR DOORS
- MOUNTING BASE FOR ANTENNA LOCATED PER SHOP ORDER
- 3.00M PORTABLE LIGHTS WITH 125" OF 1" CABLE
- DUAL BANK DUAL PRO BATTERY CHARGER LOCATED IN PLUMBING AREA
- 5/8" PROTECTIVE GUARDS FOR ALL HULL-UP DOORS
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT P1
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENTS D1, P1 & P3
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENTS D1, D2 & P1
- FIVE PLASTIC TOOL BOXES (4"x 8"x 8" & 5"x 8" & 5"x 8") ON FLOOR OF COMPARTMENT D1
- PVC TRAC ON THE REAR WALL OF COMPARTMENT P3
- ONE VERTICAL BRACKET IN COMPARTMENTS P2, P3 AND IN D5 AND P5 HATCH COMPTS.
- BACK FOR (3) AIR BAGS IN COMPARTMENT P2
- TWO ADJUSTABLE HEIGHT BRUSHED ALUMINUM SHELVES IN COMPARTMENTS D3 & P3
- L.E.D. PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- CIRCUIT BREAKER PANEL IN DRIVER SIDE FRONT BENCH COMPARTMENT
- ONE AERON ELECTRIC REWIND COIL REEL LOCATED IN HATCH COMPARTMENT ABOVE P3 WITH 200' OF 1/2" CABLE, ONE L.B. JUNCTION BOX AND WELDER
- ONE HANWAY ELECTRIC REWIND BOOSTER REEL (EP-32-23-24-12) WITH CAPACITY FOR 200' OF 1.00" WELDER-REEL TPE HOSE WITH 1.50" PIPING LOCATED IN COMPARTMENT B1
- TWO ADDITIONAL POLY TRAYS SHIPPED LOOSE
- POLISHED STAINLESS STEEL CORNER GUARDS AT REAR OF BODY
- THREE HANWAY ELECTRIC REWIND HYDRAULIC HOSE REELS MODEL 2016-17-18 WITH CAPACITY FOR 100' OF .25" I.D. DUAL HYDRAULIC HOSE LOCATED IN HATCH COMPARTMENT ABOVE D1
- KOSUMAL AIR COMPRESSOR LOCATED IN FORWARD PASSENGER SIDE HATCH COMPARTMENT
- BUSHED 5/8" SCUFFPLATE ON BACK OF CAB TOPS
- BUSHED 5/8" SCUFFPLATE CORNER GUARDS ON REAR OF CAB
- BRUSHED METAL NETTING LOCATED IN COMPARTMENT P2
- PLASTIC SHEETING HOLDER WITH CUTTING GUIDE AND KNIFE LOCATED IN COMPARTMENT D2
- TWO ADJUSTABLE 6.0" SLIDE-OUT ALUMINUM PNEUMATIC TOOLBAR LOCATED IN COMPARTMENT P3
- TWO 30A, 240V 3 PRONG 16-30 RECEPTABLES LOCATED IN HARST PUMP STORAGE AREA ON TOP OF TRUCK
- ONE 150A, 120V 6-PLACE RECEPTACLE LOCATED IN COMPARTMENT P3 AND IN HATCH ABOVE D2, TWO IN CAB

CUSTOMER APPROVAL

APPROVED BY: _____

DATE: _____

1304109	NPA	SHA	
1304909	NPA	SHA	

REV DATE BY CH ARROW XT

Pierce MANUFACTURING INC.

JOB NO. 21641

SCALE 1:24 DATE _____

CHASSIS DATA

TITLE	1500-D-500 GAL POLY, 189" RESCUE PUC BODY	DRAWN BY	NPA	Q2F609
FOR	(2) XLAYS, (1) DEADLAY, GENERATOR, BOOSTER REEL	CHECKED BY	SHA	Q2F609
MODEL	PIERCE			
DWG NO.	21641AD	SHEET SIZE	D	SHEET NO. 1 of 1