



HOSEBED CAPACITIES

- ① 300' OF 1.75" D.J. POLY HOSE
- ② 500' OF 2.50" D.J. POLY HOSE
- ③ 1000' OF 5.00" D.J. POLY HOSE

ALUMINUM BODY MAXIMUM O.A.H. 116.00" MAXIMUM O.A.L. 427.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- BATTERY CHARGER INDICATOR BEHIND DRIVER'S SEAT DISPLAYED THROUGH WINDOW
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- SIX DRIP PAN GUARDS FOR ROLL-UP DOORS LOCATED PER SHOP ORDER
- NINE FULL WIDTH/DEPTH ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER
- NINE FULL WIDTH/DEPTH ADJUSTABLE TRAYS IN COMPARTMENTS PER SHOP ORDER
- TWO ADJUSTABLE TILTING SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER
- FOUR FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER
- ONE SLIDE-OUT TOOL BOARD WITH PEGBOARD PATTERN IN COMPARTMENT PER SHOP ORDER
- ONE SWING-OUT TOOL BOARD WITH PEGBOARD PATTERN IN COMPARTMENT PER SHOP ORDER

- ONE FULL HEIGHT VERTICAL PARTITION IN COMPARTMENT PER SHOP ORDER
- ALUMINUM TREADPLATE ON THE FLOORS OF COMPARTMENT PER SHOP ORDER
- THREE ALUMINUM PEGBOARDS ON BACK WALL OF COMPARTMENT PER SHOP ORDER
- CIRCUIT BREAKER PANEL IN COMPARTMENT LS3
- FOUR 120V DUPLEX RECEPTACLES LOCATED PER SHOP ORDER
- ONE HANNAY MODEL ELFCR1622-14-16 CABLE REEL FOR 200' OF 12/3 CABLE LOCATED IN COMPARTMENT RH2
- JUMPER STUDS AT DRIVER SIDE CAB STEP
- AIR INLET/OUTLET WITH DISCONNECT COUPLING LOCATED IN DRIVER'S SIDE STEPWELL

REV	DATE	BY	CH	ENFORCER
16MAY22	JWO	COS		MAKE
20APR22	JWO	COS		PIERCE
25FEB22	JWO	PHA		MODEL

		JOB NO.	37060
		SCALE	DATE
TITLE	2000-D-750P, 720 GAL. WATER/30 GAL. FOAM CELL, DELUGE 171" FH FD, LADDERS THRU BODY, (3) SPEEDLAYS	DRAWN BY	JWO 15FEB22
FOR	BRIDGEWATER FIRE DISTRICT #3 BRIDGEWATER TOWNSHIP, NEW JERSEY	CHECKED BY	PHA 21FEB22
DWG NO.	37060AD	SHEET SIZE	SHEET NO.
		D	1 OF 1