



NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

NOTES: 1. ONAN 25KW SINGLE PHASE PTO DRIVEN GENERATOR LOCATED BETWEEN THE FRAME RAILS

MAXIMUM O.A.H. 9'-7"

SIDE ROLL AND FRONTAL IMPACT PROTECTION

CLEAR DOOR WIDTH KEY	
AMOR ROLL UP DOORS:	-2 1/4"
GORTITE ROLL UP DOORS:	-2 1/2"
PIERCE DOUBLE LAP DOORS:	-4 1/4"
PIERCE LIFT-UP LAP DOORS:	-1 1/2"
(EX: 60" F-F - 2 1/4" = 57 3/4" CLEAR) (F-F) = FRAME TO FRAME	

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

REV	DATE	BY	CH
13JAN22	SHD	DHE	MODEL
			AX8110



TITLE: HEAVY DUTY RESCUE NON-WALKIN
FOR: TOWNSHIP OF MAHWAH BID #887
BILL RING
DWG NO. 04-9822-RRLAP

JOB NO.	PRELIM
SCALE 1:24	DATE
DRAWN BY DHE	17NOV21
CHECKED BY JJF	23NOV21
SHEET SIZE D	SHEET NO. 1 OF 1