



NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

NOTES: 1. A QAN 25kw SINGLE PHASE PTO DRIVEN GENERATOR WITH A STN. STL. SPASH GUARD LOCATED BETWEEN THE FRAME RAILS.

FRONTAL IMPACT PROTECTION
MAXIMUM O.A.L.: 36' - 6.0"

CLEAR DOOR WIDTH KEY	
AMORR ROLL UP DOORS:	-2 1/4"
CORTITE ROLL UP DOORS:	-2 1/2"
PIERCE DOUBLE LAP DOORS:	-4 1/4"
PIERCE LIFT-UP LAP DOORS:	-1 1/2"
(EX: 60" F-F - 2 1/4" = 57 3/4" CLEAR) (F-F) = FRAME TO FRAME	

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH

Pierce MANUFACTURING INC.

TITLE: HEAVY DUTY RESCUE WALKIN
FOR: CRANFORD TOWNSHIP OF BID #943
DWC NO.: 70734-SH1

CHASSIS DATA: PIERCE MODEL: EN5000

DRAWN BY: SHD
CHECKED BY: GREGG CARIDDI

JOB NO.	PRELIM
SCALE: 1:24	DATE
DRAWN BY: SHD	08MAY23
CHECKED BY: -	-
SHEET SIZE: D	SHEET NO.: 1 OF 1